



HDF		HDF 40 /40-8	HDF 180 /25-35	HDF 200 /40-55	HDF 160 /70-90	HDF 90 /150-85	HDF 200 /250-280
OUTPUT CHARACTERISTICS							
Drilling fluid flow max.	l / min (U.S. gpm)	40 (10.6)	23 (6.1)	40 (10.6)	70 (18.5)	150 (39.6)	250 (66.0)
Pressure max.	bar (psi)	40 (580)	180 (2600)	200 (2900)	160 (2300)	90 (1300)	200 (2900)
Power max.	kW	2.6	7	13	19	23	85
HYDRAULIC POWER REQUIREMENTS							
Flow max.	l / min (U.S. gpm)	8 (2.1)	35 (9.3)	55 (14.5)	90 (23.8)	85 (22.5)	280 (74.0)
Pressure max.	bar (psi)	210 (3000)	210 (3000)	210 (3000)	210 (3000)	210 (3000)	210 (3000)
OVERALL DIMENSIONS							
Length	mm (in)	190 (7.5)	160 (6.3)	170 (6.7)	220 (8.7)	175 (6.9)	270 (10.6)
Width	mm (in)	315 (12.4)	245 (9.6)	280 (11.0)	330 (13.0)	365 (14.3)	745 (29.3)
Height	mm (in)	170 (6.7)	170 (6.7)	185 (7.3)	180 (7.1)	250 (9.8)	340 (14.2)
Weight	kg (lbs)	8 (17.6)	8 (17.6)	15 (33.1)	27 (59.5)	30 (66.1)	170 (374.8)