



HK / HKR		HK 450	HK 1000	HKR 1300	HKR 2000	HKR 2500	HKR 4000	HKR 5000	HKR 7500
OUTPUT CHARACTERISTICS									
Compressed air max.*	I / min (cfm)	450 (16)	1000 (36)	1300 (46)	2000 (71)	2500 (88)	4000 (141)	5000 (177)	7500 (265)
Pressure max.	bar (psi)	8 (116)	12 (174)	10 (145)	10 (145)	10 (145)	10 (145)	10 (145)	10 (145)
HYDRAULIC POWER REQUIREMENTS									
Flow at max. output	I / min (U.S. gpm)	15 (4.0)	35 (9.3)	37 (9.8)	53 (14.0)	67 (17.7)	104 (27.5)	137 (36.2)	183 (48.9)
Pressure max.	bar (psi)	210 (3000)	230 (3300)	230 (3300)	230 (3300)	230 (3300)	230 (3300)	230 (3300)	270 (3900)
OVERALL DIMENSIONS									
Length	mm (in)	530 (20.87)	725 (28.54)	490 (19.30)	490 (19.30)	490 (19.30)	650 (25.59)	670 (26.38)	779 (30.67)
Width	mm (in)	430 (16.93)	490 (19.30)	455 (17.91)	455 (17.91)	455 (17.91)	520 (20.47)	520 (20.47)	622 (24.49)
Height	mm (in)	460 (18.11)	600 (23.62)	425 (16.73)	425 (16.73)	425 (16.73)	720 (28.35)	720 (28.35)	809 (31.85)
Weight	kg (lbs)	35 (77.2)	80 (176.4)	74 (163.1)	74 (163.1)	74 (163.1)	137 (302)	137 (163.1)	270 (595.2)

HKL		HKL 400	HKL 801	HKL 1300	HKL 1300 **	HKL 1800	HKL 2600	HKL 2600 **	HKL 4100	HKL 5000	HKL 7500
OUTPUT CHARACTERISTICS											
Compressed air max.*	I / min (cfm)	400 (14)	800 (28)	1300 (46)	1300 (46)	1800 (64)	2600 (92)	2600 (92)	4100 (145)	5000 (177)	7500 (265)
Pressure max.	bar (psi)	8 (116)	8 (116)	8 (116)	8 (116)	8 (116)	8 (116)	8 (116)	8 (116)	8 (116)	8 (116)
HYDRAULIC POWER REQUIREMENTS											
Flow at max. output	I / min (U.S. gpm)	24 (6.4)	26 (6.9)	38 (10.0)	46 (12.2)	46 (12.2)	65 (17.2)	82 (21.7)	113 (29.9)	135 (35.7)	150 (39.6)
Pressure max.	bar (psi)	250 (3600)	250 (3600)	250 (3600)	250 (3600)	250 (3600)	250 (3600)	250 (3600)	250 (3600)	250 (3600)	250 (3600)
OVERALL DIMENSIONS											
Length	mm (in)	525 (20.67)	640 (25.20)	640 (25.20)	640 (25.20)	810 (31.89)	810 (31.89)	810 (31.89)	890 (35.04)	890 (35.04)	1100 (43.31)
Width	mm (in)	250 (9.84)	320 (12.60)	320 (12.60)	320 (12.60)	390 (15.35)	390 (15.35)	390 (15.35)	515 (20.28)	515 (20.28)	890 (35.04)
Height	mm (in)	325 (12.80)	520 (20.47)	520 (20.47)	520 (20.47)	620 (24.41)	620 (24.41)	620 (24.41)	790 (31.10)	790 (31.10)	900 (35.43)
Weight	kg (lbs)	30 (66.1)	55 (121.3)	55 (121.3)	55 (121.3)	103 (227.1)	103 (227.1)	103 (227.1)	185 (407.9)	185 (407.9)	330 (727.6)

* ISO 1217.

** Low pressure model (nominal hydraulic input pressure 170 bar.)