DEMOLITION SORTING GRAB HSG

Silent Demolition and Sorting/Loading Grapple

■ With 360 degree rotator, operator can align jaws without moving machine and pick material from any angle.

■ With synchronized jaws, operator can pick small items and place very precisely.



604-888-9020 sales @vanedequipment.com







Model		Unit	HSG13R	HSG21R
Recommended Carrier		Metric Ton	8~15	16~22
Weight		kgs	1,040	1,580
		lbs	2,288	3,480
Opening		mm	1,900	2,130
		inch	75	84
Width		mm	900	1,000
		inch	35	39
Depth		mm	520	625
		inch	20	25
Areal Capacity		m²	0.60	0.80
		yd²	0.78	1.04
Volume Capacity		liter	540	800
		yd³	1.57	2.35
Jaw	Rated Pressure	bar	350	350
		psi	5,080	5,080
	Rated Flow	lpm	80	120
		gpm	21	31
	Closing Force	Metric Ton	5.2	7.0
		lbs (x1,000)	2.36	3.18
Rotator	Rated Pressure	bar	170	170
		psi	2,465	2,465
	Rated Flow	lpm	17	35
		gpm	4	9
	Speed	RPM	12	12
Specifications are subject to change without notice.				

Specifications are subject to change without notice.