

Technical specifications:

Rototilt RT10

Fixed upper - S40 coupler



Rototilt RT10 Fixed-S40

RT10 Fixed-upper S40 Coupler	
Min/max machine weight	1,500 - 3,500 kg / 3,310 - 7,715 lb
Max bucket volume	0.12 m ³ / 0.16 yd ³
Max bucket width	1.0 m / 39.4 in.
Max break out force	35 kN / 7,870 lbf.
Weight (approx.)	110 kg / 243 lb
Tilt angle	2 x 40°
Rotation	unlimited
Rotation speed	1 revolution per 7 seconds @ 15 l/min (3.96 gpm)
Operating pressure	21 MPa / 3045 psi
Max return line pressure	2 MPa / 290 psi
Rotation torque	approx. 1,700 Nm / 1,255 ft.lb @ 21 MPa / 3045 psi
Tilt torque	5,800 Nm / 4,280 ft.lb
Recommended hydraulic flow	20 l/min / 5.28 gpm

Technical specifications:

Rototilt **RT20B**

Multi upper - S40 coupler



Rototilt RT20B Multi-S40

	RT20B Multi-upper S40 Coupler
Min/max machine weight	3,000 - 6,000 kg / 6,615 - 13,230 lb
Max bucket volume	0.2 m ³ / 0.26 yd ³
Max bucket width	1.2 m / 47.2 in.
Max break out force	45 kN / 7,870 lbf.
Weight (approx.)	155 kg / 342 lb
Tilt angle	2 x 40°
Rotation	unlimited
Rotation speed	1 revolution per 7 seconds @ 30 l/min (7.93 gpm)
Operating pressure	25 MPa / 3625 psi
Max return line pressure	2 MPa / 290 psi
Rotation torque	approx. 3,900 Nm / 2,880 ft.lb @ 25 MPa / 3625 psi
Tilt torque	14,400 Nm / 10,620 ft.lb
Recommended hydraulic flow	40 l/min / 10.57 gpm