

# Heavy-Duty Power Angle Broom



Oscillating design allows broom to follow uneven terrain while maintaining contact with the ground



This contractor grade broom has a 14 gauge steel head, oversized bearing and floating tilt that follows the uneven surface for better bristle contact.


Heavy-Duty storage stands fold down easily



Great addition to your snow clearing fleet



Take a Picture of This QR Code With Your Smart Phone to See it in Action



Hood made from **14 Gauge steel** and formed for added strength

More robust and larger diameter **filament** than most of our competitors

Multiple heavy-duty **wafer packages** available

Flip up storage **stand**, no snap pins needed

Oversized 2" bearing on arbor



**Direct-drive design** with replaceable drive components allowing forward and reverse operation



*Optional:* Wire Harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/Bobcat (14-pin).



*Optional:* Pistol Grip Control Harness is required if skid steer is NOT equipped with attachment control system. (Only needed when ordering hydraulic angling model).

## FEATURES & BENEFITS

- 8° floating tilt allows broom to follow ground contour. This helps prevent bristle coning when angled
- Float & Tilt allows control of right to left as well as up and down movement
- Stronger reinforced frame
- Handles on bearing help with arbor change
- Handles on motor can help with bearing change and help protect motor
- Easy flip down stands require no tools and no pins
- Angle side to side 30 degrees
- Larger 3" hex drive helps with longevity
- Wafer packages available in poly, poly/ steel and steel

## SPECIFICATIONS / OPTIONS

Model	720HD / 720HDX / 720HDXL	840HD / 840HDX / 840HDXL	960HD / 960HDX / 960HDXL
Width	72"	84"	96"
Width Fully Angled	62" @ 30°	72.5" @ 30°	83" @ 30°
Broom Angle	Manual 30° / Hyd 30° / Hyd 30°	Manual 30° / Hyd 30° / Hyd 30°	Manual 30° / Hyd 30° / Hyd 30°
Drive System	Hydraulic Motor Direct-Drive	Hydraulic Motor Direct-Drive	Hydraulic Motor Direct-Drive
Skid Steer Flow Range	13-24 GPM	13-24 GPM	13-24 GPM
Wafer Diameter	32"	32"	32"
Wafer Sections (number)	38	44	50
Shipping Weight	1,040 - 1,115 lb.	1,120 - 1,200 lb.	1,205 - 1,275 lb.
Reversible Valve Block	Included w/XL model	Included w/XL model	Included w/XL model

### Options

Pistol Grip Control Harness\*

Loader Specific Wire Harness\*

Replacement Wafers

Factory Installed Couplers

\*Applies to Hydraulic Models Only

\* For more specification details please see our website [www.erskineattachments.com](http://www.erskineattachments.com)