


FECON BULL HOG® EXCAVATOR MULCHING HEAD 8-15 Ton



STANDARD CONFIGURATION

- FGT Rotor with Double Carbide Tools
- Variable Displacement 55cc Hydraulic Motor
- Efficiently Mulch up to 6" Material
- Adjustable Hydraulics to Match Carrier Flow and Pressure
- Configurable for 8-15 T Excavators and Boom Arms
- Built with 100 ksi High Strength Steel
- Fecon Standard Warranty – 12 months / 1,000 hours

QUICK SPECIFICATIONS

	CEM36
Excavator Working Class	8-15 ton
Working Width	36"
Overall Width	57"
Weight	1450 lbs
Flow Range	17-40 gpm
Max Pressure	6000 psi
Standard # of Tools	18

Pricing and Specifications are subject to change without notice.

Pricing listed in US Dollars (\$).

When placing orders, carrier model must be noted to receive correct mount, hoses, and QD's.

The Extended Warranty Program is underwritten by Am Trust International and administered by Glynn General Corporation.

SAFETY IS THE RESPONSIBILITY OF THE OPERATOR. Always ensure your carrier's safety features, including ROPs & FOPs, meet your job safety requirements.

A minimum of 1/2" Polycarbonate Guarding for operator protection is required for all attachments, except for the Fecon Stumpex® product line.

Auxiliary equipment options or attachments not listed may be quoted upon request.