

A GRYB COM<u>PANY</u>

WOODRAKE POWER GRAPPLE

BPG-WR MODELS





2 YEAR/3,000 HOURS WARRANTY.



CONTACT US

(705) 487-5020 BATEMANMANUFACTURING.COM MAIL@BATEMANMANUFACTURING.COM

WORK WITH CONFIDENCE

CUSTOM ATTACHMENT SOLUTIONS AVAILABLE TO MEET YOUR UNIQUE SPECIFICATIONS/APPLICATIONS. WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND TO IMPROVE OUR PRODUCTS WITHOUT NOTICE OR OBLIGATION.

WOODRAKE POWER GRAPPLE BPG-WR MODELS **



The BATEMAN Woodrake (WR) Series is built to handle the toughest of forestry applications. Whether grubbing, working on a ROW, laying down mats, feeding a grinder or chipper, or cleaning up a landing, the WR Series of grapples can handle it. This grapple can be outfitted with the Hultdins SuperSaw 555s or 650s. With our proportional simultaneous valve, this grapple can run from a single circuit.



	BPG100- 32WR-056	BPG100- 32WR-062	BPG160- 32WR-068	BPG160- 43WR-068	BPG200- 32WR-072	BPG200- 43WR-072	BPG300- 32WR-086	BPG300- 43WR-086	BPG300- 43WR-096	BPG400- 43WR-116
Machine Class	3t - 10t	5t - 20t	5t - 20t	5t - 20t	9t - 50t	9t - 150t	13t - 150t	13t - 150t	25t - 150t	25t - 150t
Max Opening in (mm)	56 (603)	62 (667)	68 (732)	68 (732)	72 (775)	72 (775)	86 (926)	86 (926)	96 (1,033)	116 (1,249)
Width in (mm)	24 (258)	26 (280)	23 (248)	29 (312)	27 (291)	36 (388)	34 (366)	40 (431)	42 (452)	42 (452)
Tine By-Pass Configuration	3/2	3/2	3/2	4/3	3/2	4/3	3/2	4/3	4/3	4/3
Area Tip-To-Tip ft.² (m²)	3.3 (.03)	4.1 (0.4)	4.7 (0.4)	4.7 (0.4)	5 (0.5)	5 (0.5)	6.6 (0.6)	6.6 (0.6)	10 (0.9)	12 (1.1)
Cylinder Size in (mm)	3 (32)	3 (32)	3.5 (38)	3.5 (38)	3.5 (38)	3.5 (38)	4 (43)	4 (43)	4 (43)	5 (54)
Cylinder Max. Pressure PSI (bar)	3,000 (207)	3,000 (207)	3,000 (207)	3,000 (207)	5,000 (345)	5,000 (345)	5,000 (345)	5,000 (345)	5,000 (345)	5000 (345)
Weight Ib (kg)	720 (327)	830 (376)	1,200 (544)	1,340 (608)	1,970 (894)	2,260 (1,025)	3,150 (1,429)	3,380 (1,533)	4,400 (1,996)	4,800 (2,177)
Saw Bar Option	555 650	555 650	555 650	555 650	555 650	555 650	555 650	555 650	555 650	555 650

