

GAS DUST/ODOR CONTROLLER







GAS DUST/ODOR CONTROLLER

- OSCILLATION UP TO 270°
- POWERFUL & VERSATILE
- STANDARD GARDEN HOSE HOOK-UP



GASOLINEDUST/ODOR CONTROLLER

TOP BENEFITS

- Powerful and versatile
- Easy to operate and maintain
- Self contained
- · Requires only standard water pressure
- 10 year manufacturer warranty

TOP FEATURES

- High speed oscillation up to 270°
- · Non-oscillating option available
- 3 wheel off-road trailer package for ease of transport
- 6 gallon fuel capacity
- · Standard garden hose hookup

GENERAL INFO

- Oscillation: 180° (capable of 270° upon request)
- Hand held wireless transmitter (water resistant) with push button control (manual control option available)
- · Min/Max water pressure: 40 psi 120 psi
- Min/Max water volume: 1/3 gallon -20 gallons per minute at 120 psi
- Throw distance (neutral wind conditions):
 Vertical-up to 50 ft / Horizontal-up to 125 ft
- Gyratory atomizing nozzle system
- · Outlet size: 12"
- Hose input: 3/4" utility / garden hose
- Droplet size: 50 200 microns

ENGINE SPECS

- Engine start/stop function (no choke required)
- ECH749 Kohler Gasoline Engine
- 26.5 HP Fuel Injected Engine
- Adjustable throttle up to 3900 RPM (more fuel economy when ran at 3600 RPM)
- 3 year engine warranty

PHYSICAL SPECS

- Frame length: 48"
- Overall length w/nozzle: 126" (105" w/handle turned to the side for transporting)
- Length w/out wheels and handle: 76"
- Max width: 48" (34" w/wheels and handle removed)
- Max height w/nozzle in upright position: 58"
- Weight: 800 lbs.

Applications

Demolition Sites • Landfills • Wood Recycling Scrap Metal Recycling • Aggregate Processing Waste Transfer • Indoor Recycling Facilities

OPTIONS





Fork Lift Pockets

Lifting Bracket



300 Gallon Tank















