

VAN-ED V-SERIES HAMMERS

ITEMS	MODEL	V45F	V57FX	V70F	V75F	V80F
Operation Weight	LB	311	406	717	908	1,143
Overall Length	INCH	48	55	64	67	75
Energy Class	ft.lb	250	400	550	875	1,000
Relief Settings	PSI	2,500	2,500	2,500	2,500	2,500
Oil Flow	GPM	4-7	6-16	8-16	9-18	10-22
Blow Rate	BPM	550-1000	600-1500	380-1,000	380-900	400-1,100
Operating Pressure	PSI	1,280-1,707	1,280-1,707	1,565-2,347	1,707-2,347	1,991-2,418
Tool Diameter	INCH	1.77	2.24	2.75	2.95	3.15
Suitable Carrier	TON	0.8-2.5	1.5-4	3-6.5	4.5-8	4.5-8

ITEMS	MODEL	V90F	V105F	V115F	V135F	V135FX
Operation Weight	LB	1,323	2,231	2,714	3,477	4,068
Overall Length	INCH	83	90	97	107	111
Energy Class	ft.lb	1,400	2,500	4,500	5,000	5,500
Relief Settings	PSI	2,500	3,000	3,000	3,000	3,000
Oil Flow	GPM	11-22	18-31	22-34	27-35	32-43
Blow Rate	BPM	350-1,000	350-550	320-550	320-480	320-550
Operating Pressure	PSI	1,991-2,418	1,991-2,702	1,991-2,702	2,276-2,702	2,276-2,702
Tool Diameter	INCH	3.54	4.13	4.52	5.31	5.31
Suitable Carrier	TON	6-10	10-15	12-18	18-24	20-26

ITEMS	MODEL	V145F	V155F	V165F	V175F	V180F
Operation Weight	LB	4,456	6,107	7,688	9,037	9,890
Overall Length	INCH	116	125	134	142	148
Energy Class	ft.lb	6,500	8,000	10,000	12,000	14,000
Relief Settings	PSI	3,000	3,300	3,300	3,000	3,000
Oil Flow	GPM	34-47	45-58	49-63	54-72	58-81
Blow Rate Per Minute	BPM	270-500	230-400	230-345	230-330	270-380
Operating Pressure	PSI	2,276-2,702	2,276-2,702	2,134-2,702	2,134-2,702	2,134-2,702
Tool Diameter	INCH	5.7	6.1	6.5	6.88	7.08
Suitable Carrier	TON	22-30	28-42	34-50	40-60	45-80



604-888-9020
sales@vanedequipment.com