

DEMOLITION & SORTING GRAPPLE

Extractor



www.amiattachments.com



20
YEARS
EST. 2001



Extractor

OUTSTANDING STRENGTH
PRECISE CONTROL
GREATER PAYLOAD, LOWER FUEL

High performance strength meets cutting-edge agility with AMI Attachments' Extractor - the versatile demolition and sorting grapple capable of taking down buildings, moving large volumes of material, and picking through fine recyclables.

Built for strenuous work, the Extractor is made with Hardox® Wear Plates and Strenx™ steel and moves higher volumes of material using less fuel - cycle after cycle. The Extractor rotates 360 degrees and features flexible jaw operation with edge-to-edge contact, reversible cutting edges, and zero clearance design for maximum productivity.


DEMOLITION • PRECISE SORTING
MASS LOADING • RECYCLING



STRENX™

HIGH PERFORMANCE STEEL

Made with Strenx™, a recognized high-performance steel, the Extractor is both structurally lighter and stronger than regular T1 steel grapples. This impressive strength to weight ratio means efficient operation with lower fuel used per volume moved.



EDGE-TO-EDGE CONTACT

The Extractor's precision edge-to-edge contact makes selecting thin and valuable items incredibly easy.

REVERSIBLE CUTTING EDGES



HARDOX WEAR PLATE

High-wear serrated edges and mounting edges are made with Hardox® Wear Plate, an abrasion-resistant steel that can repeatedly withstand the Extractor's rigorous work.



360° ROTATION

For exceptional performance and total operator control, the Extractor rotates 360 degrees to position the grapple accurately and move loads quickly.




VERTICAL TINES

With the Extractor's zero clearance jaw design, operators can easily retrieve objects tightly positioned against walls and bins with its perfectly vertical jaw opening.

AMI EXTRACTOR DEMOLITION & SORTING GRAPPLE SPECIFICATIONS CHART

EX Series	Rotator	Open Height (A)	Max Opening (B)	Closed Width (C)	Closed Height (D)	Jaw (E)	Weight
130-150	XR400	47 in	72 in	46 in	22 in	32 in	2,300 lbs
200	XR500	50.5 in	80 in	50.5 in	30 in	36 in	2,900 lbs
250-300	XR500	70 in	88 in	60 in	41.5 in	54.5 in	4,600 lbs
300-400	XR600	72 in	94 in	62 in	46 in	60 in	4,800 lbs

Extractor



OTHER DEMOLITION ATTACHMENTS



DEMOLITION GRAPPLE



CONCRETE PULVERIZER



INTERGRATED THUMB BUCKET



Authorized Dealer



1.800.556.9452

Phone: (519) 699-0387 Fax: (519) 699-0440
1270 Geddes St., Hawkesville, ON, Canada NOB 1X0

www.amiattachments.com



#amiattachments