



1235 mm



880 mm





985 mm

SPECIFICATIONS

	Recommended excavator	ton	7 - 11
	Weight	ton	0,72
	Load capacity	m ³	0,35
	Pressure	bar	200 - 250
	Oil flow rate*	l/min.	75 - 100

* The minimum hydraulic flow rate value must be alongside the required operating pressure

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
 RQ8/RQ20/RQ50 Sifting kit	8/20/50 mm	Sifting damp/dry soil Soil aeration
 RM Mixer kit	-	Soil aeration Compost aeration Charcoal reduction Glass reduction Drywall reduction
 RE8/RE16 Fine Sifting kit	8/16 mm	Sifting damp/dry soil
 RC Compost kit	36,5 mm	Shredding foliage and small branches Composting

* Shafts in closed position.

ACCESSORIES

RQ8/RQ20/RQ50 Sifting kit	RM Mixer kit
RE8/RE16 Fine Sifting kit	RC Compost kit
Shaft holder	24 Month Warranty

APPLICATION AREAS



ROAD WORKS



TUNNELS



ENCLOSED SPACES



PIPELINES

RECYCLING
AGGREGATES

EXCAVATION

URBAN
CONSTRUCTION SITES

FOUNDRIES

MAINTAINING LANDSCAPE
AND AGRICULTURAL AREAS