GRM SERIES

ROTARY MOWER

Fearlessly slash through stringy, green brush and navigate muddy, wet conditions with the GRM Rotary Mower. This combo allows you to cut through more than just grass while above water, and scoop debris or gain footing while within water. After the day is done, don't expect to need any time in the shop after hours, buffing dents out or ordering and replacing worn parts.



33 OR 50" **CUTTING WIDTH**

8 - 15 ton **EXCAVATORS**





PROMACEQUIPMENT.CA / GRM

KEY SPECS: GRM 33 GRM 50 MIN:8 | MAX:15 **EXCAVATOR SIZE (TONS)** MIN:8 | MAX:15

CUT WIDTH (INCHES) 50 MIN. WEIGHT (POUNDS) 1040 (FLAT-TOP BRACKET) 1380 (FLAT-TOP BRACKET)

STD. MOTOR TYPE VARIABLE DISPLACEMENT VARIABLE DISPLACEMENT 55 55 STD. MOTOR SIZE (CC)

AVG. FLOW RANGE (GPM) 13-26 20-26 MIN. PRESSURE (PSI) 3000 3000 (RPM) SUGGESTEO BLADE SPEED 1800 1800

WETLAND CONTRACTOR'S CHOICE



BUILD & COMPONENTS

STANDARD

1/2" THICK AR400 DIRECT DRIVE W/ 28 OR 45CC FIXED FLAIL RLADES PERFORMANCE COUPLER

INTEGRATED PUSHER/ FLAT-TOP BRACKET

PIVOT POINT DISPLACEMENT MOTOR

NPTINNAL

DISPLACEMENT MOTOR **OUICK CHANGE OR** PIN TYPE BRACKET

75CC VARIABLE

DESIGN

REINFORCED DECK

WATER-RESISTANT

SFAIS

LIFTED CORNER **GUIDED INPUT**

USE CASES

WETLAND **PUBLIC WORKS**

SHORELINE MAINTENANCE

DRAINAGE MAINTENANCE



