


SORTING GRAPPLE

MB-G500 S4









SPECIFICATIONS

Recommended excavator	ton	5 - 8
Weight	ton	0,42
Capacity (claws closed)	m^3	0,18
Rotation	Degree	360°
Oil pressure (rotation)	bar	160 - 200
Oil flow rate (rotation)	l/min	15 - 25
Oil pressure (opening - closing)	bar	180 - 250
Oil flow rate (opening - closing)	l/min	30 - 40
Size A	mm	1500
Size B	mm	980
Size C	mm	415
Size D	mm	1095
Size E	mm	855
Size F	mm	530
Size G	mm	555

OPTIONAL ACCESSORIES

Multi-purpose blade kit	Clam shell kit
Serrated side plate kit	Grip improvement kit
Rubber protection kit	Serrated side profile kit
12 V Electrical Kit (for 2 hose functionality)	24 Month Warranty

APPLICATION AREAS

Demolitions and Renovations

Road works and Infrastructures

Enclosed Spaces

Urban Construction Sites

Pipelines

Inert materials recycling and Waste management

Agriculture and Landscaping

Forest maintenance

EN

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice. It is the responsibility of the installer to verify the suitability of the carrier machine with regard to the weight and specifications of the attachment.