

## SHAFTS SCREENER

# MB-HDS407





A




## SPECIFICATIONS

| | | |
|---|---|---|
| Recommended excavator | ton | 3,5 - 5,5 |
| Recommended backhoe loader | ton | 6 - 9* |
| Weight** | ton | 0,28 |
| Load capacity | m³ | 0,14 |
| Pressure | bar | 200 - 220 |
| Back pressure | bar | < 20 |
| Oil flow rate*** | l/min | 25 - 35 |
| Size A | mm | 765 |
| Size B | mm | 840 |
| Size C | mm | 760 |

* Only compatible with the posterior boom of a Backhoe.
** The package includes an RQ Shaft Kit. The weight may vary based on the installed kit.
*** The minimum hydraulic flow rate value must be alongside the required operating pressure.

## SHAFT KIT

| KIT | ADJUSTMENT* | APPLICATION |
|---|---|---|
| RQ15 Sifting kit | 15 mm | Sifting damp/dry soil<br>Soil Aeration |
| RM Mixer kit | | Coal reduction<br>Soil Aeration<br>Compost Aeration<br>Glass reduction<br>Drywall reduction |
| RQ8 Sifting kit | 8 mm | Sifting damp/dry soil<br>Soil Aeration |

* Shafts in closed position.

## OPTIONAL ACCESSORIES

| | |
|---|---|
| RQ8 Sifting kit | RQ15 Sifting kit |
| RM Mixer kit | 24 Month Warranty |

EN

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice. It is the responsibility of the installer to verify the suitability of the carrier machine with regard to the weight and specifications of the attachment.

MBCRUSHER.COM

Rev. 20261028