

DRUM CUTTER
MB-R500





A



C

B



SPECIFICATIONS

Recommended excavator	ton	3,5 - 11
Recommended skid steer loader*	ton	3,5 - 6
Weight	ton	0,30
Pressure**	bar	300 - 350
Back pressure	bar	< 4
Oil flow rate***	l/min	60 - 120
Cutting width	mm	450
Speed/Min. (minimum - maximum)	rpm	80 - 120
Output torque	kNm	5
Drum diameter	mm	500
Cutting force****	kN	19,6
Size A	mm	500
Size B	mm	500
Size C	mm	820

* Please verify machine's Rated Operating Capacity.
** Output torque and cutting force decrease as the operating pressure decreases.
*** The minimum hydraulic flow rate value must be alongside the required operating pressure.
**** Cutting force at tooth tip.

OPTIONAL ACCESSORIES

Dust suppression kit	Interchangeable drum kit (low-set / full-set)
Rock and asphalt picks kit	Drum cover kit
Cutting depth adjustment kit	Cutter body rotation kit
Power transmission kit	24 Month Warranty

APPLICATION AREAS

Demolitions and Renovations
Road works and Infrastructures
Enclosed Spaces
Urban Construction Sites
Remote Areas and Complex Logistics
Pipelines
Foundries
Agriculture and Landscaping
Forest maintenance

EN

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice. It is the responsibility of the installer to verify the suitability of the carrier machine with regard to the weight and specifications of the attachment.