

DRUM CUTTER
MB-R900





A



C

B



SPECIFICATIONS

Recommended excavator	ton	19 - 35
Weight	ton	1,40
Pressure*	bar	300 - 350
Back pressure	bar	< 4
Oil flow rate**	l/min	250 - 350
Cutting width	mm	1130
Speed/Min. (minimum - maximum)	rpm	60 - 80
Output torque	kNm	13,2
Drum diameter	mm	680
Cutting force***	kN	40
Size A	mm	1130
Size B	mm	680
Size C	mm	1375

* Output torque and cutting force decrease as the operating pressure decreases.
** The minimum hydraulic flow rate value must be alongside the required operating pressure.
*** Cutting force at tooth tip.

OPTIONAL ACCESSORIES

Dust suppression kit	Interchangeable drum kit (low-set / full-set)
Rock and asphalt picks kit	24 Month Warranty

APPLICATION AREAS

Demolitions and Renovations
Road works and Infrastructures
Quarries and Mines
Enclosed Spaces
Urban Construction Sites
Remote Areas and Complex Logistics
Pipelines
Foundries
Agriculture and Landscaping
Forest maintenance

EN

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice. It is the responsibility of the installer to verify the suitability of the carrier machine with regard to the weight and specifications of the attachment.