

DRUM CUTTER
MB-R500





A



C

B



SPECIFICATIONS

Recommended excavator	lb	7,720 - 24,250
Recommended skid steer loader*	lb	7,720 - 13,230
Weight	lb	661
Cutting width	in	18
Speed/Min. (minimum - maximum)	rpm	80 - 120
Output torque	kNm	5
Pressure**	PSI	4,351 - 5,076
Back pressure	PSI	< 58
Oil flow rate***	gal/min	16 - 32
Drum diameter	in	20
US- Cutting force****	kN	19,6
Size A	in	20
Size B	in	20
Size C	in	32

* Please verify machine's Rated Operating Capacity.
** Output torque and cutting force decrease as the operating pressure decreases.
*** The minimum hydraulic flow rate value must be alongside the required operating pressure.
**** Cutting force at tooth tip.

OPTIONAL ACCESSORIES

Dust suppression kit	Interchangeable drum kit (low-set / full-set)
Rock and asphalt picks kit	Drum cover kit
Cutting depth adjustment kit	Cutter body rotation kit
Power transmission kit	24 Month Warranty

APPLICATION AREAS

Demolitions and Renovations
Road works and Infrastructures
Enclosed Spaces
Urban Construction Sites
Remote Areas and Complex Logistics
Pipelines
Foundries
Agriculture and Landscaping
Forest maintenance

EN

The data and images provided above are not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice. It is the responsibility of the installer to verify the suitability of the carrier machine with regard to the weight and specifications of the attachment.